

Exploring Nonlinear Dynamics of Information Flow in Distributed Academic and Library Service and Information Source Networks

K. Sundareswari

Professor in Mathematics, Al-Ameen Engineering College (Autonomous), Erode, Tamilnadu, India.

KEYWORDS:

Nonlinear Dynamics;
Information Flow;
Distributed Networks;
Academic Libraries;
Library Services;
Information Source Networks;
Information Systems;
Complex Networks

Author's Email:

sundarimaths@gmail.com

Received : 04.04.2026

Revised : 06.05.2026

Accepted : 08.06.2026

ABSTRACT

Distributed academic and library service networks have grown to be complex digital spaces that incorporate digital libraries, institutional repositories, research-data platforms, cloud-based services, authentication systems, metadata systems, and distributed scholarly information providers. The more these services are interconnected, the more the interacting factors of information-flow performance such as service demand, communication delay, resource availability, security disturbance, recovery behavior, etc. have an impact. The paper forms a nonlinear dynamical model to explore the combined influence of these factors on the behavior of distributed academic and library information-service networks. The proposed model represents the relationships between workload, resource consumption, latency, service continuity, disturbance effects and recovery mechanisms between the operating conditions in a couple way. There are seven performance metrics used to conduct the computational evaluation i.e., Information throughput, average response time, resource utilization, service availability, stability index, recovery time, and resilience index. The analysis looks into normal operation, increasing demand, resource-constrained conditions, disturbance scenarios, and recovery processes to determine stable, transitional and degraded operating regions. The findings are to be used to demonstrate nonlinear interactions patterns, saturation effects and recovery properties but not to advertise the establishment of validation of a particular deployed institutional network. The framework is a logical foundation of the insights into performance stability and resilience of the distributed academic libraries, institutional repositories, and research-data service environments.

How to cite this article: Sundareswari K, Exploring Nonlinear Dynamics of Information Flow in Distributed Academic and Library Service and Information Source Networks, Applied Nonlinearity in Science and Technology, Vol. 2, No. 2, 2026, 9-18

1. INTRODUCTION

The academic and library service environments are more and more reliant on interrelated digital infrastructures that facilitate access to scholarly information, institutional repositories, research-data platforms, metadata services, authentication systems, and cloud-based resources. These services allow users to find, access, store as well as share information through various institutional and Internet-based systems. With the growth in the number of users, digital resources and distributed services, there is a growth in the complexity of information flow, and is heavily reliant on the coordinated network and computational resources.

Such environments are affected by the service demand, communication delay, resource utilization, service availability, and disturbances on security. Information requests can be effectively handled at a low or moderate work load, but as workload grows, congestion, resource saturation, increased response time and decreased service availability can occur. Faults involving authentication, communication connections, servers or repositories can also cause failure in information flow and initiate recovery procedures. Such interactions are not necessarily proportional and a simple linear description of such systems is insufficient to compute the dynamic behavior of distributed academic information systems.

The current literature tends to study the digital-library performance, cloud services, information retrieval, network security, and distributed information systems as independent research topics. The nonlinear interaction between service load, latency, resource constraints, availability, disturbance and recovery in a single academic and library service-network has received relatively little attention. As such, this paper constructs a nonlinear dynamical model to investigate information-flow behavior when subjects are operating normally, overloaded, disturbed and in recovery conditions.

The most notable results of this work are the creation of a coupled nonlinear model of distributed academic and library information services, its assessment by Information Throughput, Average Response Time, Resource Utilization, Service Availability, Stability Index, Recovery Time, and Resilience Index, and the discovery of stable, transitional, and degraded operating space under varying service conditions and recovery and resilience post-disturbance behavior. The study offers a mathematical foundation on the interaction of nonlinear factors on performance and stability of academic libraries, institutional repositories, and research-data service environments.

2. RELATED WORK

The academic and library services are more and more distributed on the basis of interlinked repositories, digital platforms, metadata system, and sources of scholarly information. Complex-system analysis has demonstrated that compact dynamical models can be used to model the interaction between several states of a network [1]. Population-dynamic, epidemic-based, model-selection, and ordinary differential-equation models have also been used to model information-diffusion behavior [4], [7], [12], and [14].

The performance of information flowing is influenced by network structure, time constraints, competing propagation mechanisms, and nonlinear interactions. Diffusion of financial information has been studied in multifaceted social networks [2] and the diffusion of crisis-information has been studied under dynamic diffusion circumstances [3]. Social networks have also explored the problem of nonlinear anomalous diffusion [5]. The diffusion between the information processes of more than two has been competitive studied in [10], time and content constraints have been integrated in [9], and dynamic multi-agent diffusion has been researched in [15]. Wider scans have also pointed out the connection between the

diffusion processes and the network susceptibility [11].

The appropriate stability and resilience of systems is particularly relevant in cases where information networks are working on growing load or perturbation. The ability of complex networks to behave as universal resilience has been explored in [6]. The instability of Turing-type and reaction-diffusion has been studied in [8], and the nonlinear dynamic control and stability changes in information propagation have been studied in [13]. These experiments show that adjustments to the strength of interactions, the strength of disturbances, and the strength of response mechanisms can cause a system to shift between stable and unstable operating points.

This creates a gap in research since most of the available literature covers social, financial, crisis, rumor or commercial networks as opposed to distributed academic and library service setting. Even though separate studies cover diffusion [2], nonlinear behavior [5], resilience [6], instability [8], vulnerability [11], and dynamic control [13], there is little that considers Information Throughput, Average Response Time, Resource Utilization, Service Availability, Stability Index, Recovery Time, and Resilience Index through a single nonlinear model. This paper fills this gap by presenting a model of the joint impact of demand, delay, availability of resources, disturbance, service continuity, and recovery on distributed academic and library information-service networks.

3. SUGGESTED NONLINEAR INFORMATION-FLOW MODEL

3.1 Distributed Service Network Representation

The academic and library information environment is depicted as a distributed network of services that are interconnected and assist in the flow of scholarly information between users and heterogeneous information sources. It consists of users and researchers, access interfaces, authentication services, metadata and discovery services, institutional repositories and digital libraries and research-data platforms, cloud-based resources, and external scholarly information. An example of a user request involves an entry into the system via an access service, authentication, metadata-processing, and is forwarded to a single or multiple information sources to be retrieved and delivered. Due to these

interrelations, only a single part of the network may affect the overall performance of the information-flow, were congestion, resource constraints, interrupt in services, or delays in communication can occur.

The main elements and information-flow directions that will be taken into account within the model are depicted in Figure 1.




Fig. 1. Distributed Academic and Library Service Network Architecture

3.2 Dynamic State Variables

The changing condition of the distributed information network is represented using seven principal state variables: information demand $D(t)$, information-flow rate $F(t)$, communication delay $L(t)$, resource availability $R(t)$, security disturbance $S(t)$, service availability $A(t)$, and recovery behavior $Q(t)$. These variables collectively describe the operational state of the system at a particular time.

The overall state vector is defined as

$$X(t) = [D(t), F(t), L(t), R(t), S(t), A(t), Q(t)]^T. \quad (1)$$

The rise in demand may increase resource utilization and delay in communication whereas a lack of resources and disturbances may decrease throughput

and availability. Recovery mechanisms assist in restoration of performance of services once disrupted.

3.3 Coupled Nonlinear Dynamics

The interaction among the dynamic variables is represented using a general nonlinear state-space formulation:

$$\frac{dX(t)}{dt} = F(X(t), \theta), \quad (2)$$

where $X(t)$ represents the system state vector and θ contains the model parameters controlling demand growth, resource capacity, delay effects, disturbance intensity, service restoration, and recovery behavior.

The nonlinear model formulation enables the model to include the relevant behavior of saturation of resource, swift increase in the latency with high

demand, service availability degradation during disturbances and smooth reintegration of the model to the normal operating conditions. Specifically, throughput is considered to be dependent on service demand, available resources, service availability, communication delay and disturbance intensity. The model allows this coupling to capture those instances where a small change in demand or disturbance can cause disproportionately large changes in system performance.

3.4 Model parameter and assumptions

The main model parameters include the growth of service-demand, resource capacity, load-delay interaction, disturbance growth, security response and recovery strength. In the computational model,

state variables are normalized and the base is a stable, baseline state, where the information demand is moderate, resource availability is adequate, communication delay is low, service availability is high, disturbance is not too high and recovery activation is limited.

Incoming demand is not represented as a measure of demand in a particular institution but as an aggregate measure of requests in academic and library information services. Similarly, security disturbance is a generalized service disruption, and is not designed to recreate a specific real-world cyberattack. Table 1 summarizes the parameter values and initial conditions that the computational study uses.

Table 1. Model Parameters and Initial Conditions

Symbol	Description	Representative Value/Range
$D(0)$	Initial information demand	0.35
$F(0)$	Initial information-flow rate	0.60
$L(0)$	Initial communication delay	0.20
$R(0)$	Initial resource availability	0.85
$S(0)$	Initial disturbance intensity	0.05
$A(0)$	Initial service availability	0.95
$Q(0)$	Initial recovery state	0.10
λ	Service-demand coefficient	0.20-0.60
μ	Load-delay coefficient	0.20-0.50
ρ	Resource-capacity/recovery coefficient	0.30-0.60
ξ	Disturbance-growth parameter	0.10-0.50
ω	Security-response coefficient	0.30-0.60
χ	Recovery coefficient	0.30-0.60

4. COMPUTATIONAL METHODOLOGY

4.1 Computational Environment

The suggested nonlinear information-flow model is assessed by a controlled computational simulation meant to simulate the particular operating circumstances in distributed academic and library service networks. The numerical process starts by returning the initial state of the system, model parameters, level of service demand, state of resource capacity, level of disturbance and recovery coefficients. The nonlinear state equations (coupled)

are then solved iteratively within the chosen simulation period and the state trajectories obtained are utilized in the calculation of information-flow performance, system stability, service degradation, and recovery behavior. The operating conditions are assessed individually in order to compare changes in throughput, delay, resource utilization, availability, stability and resilience when operating conditions are maintained with constant numerical parameters. Figure 2 shows the entire computational process, involving model setup, nonlinear simulation, scenario run, metric computation and stability test.




Fig. 2. Computational Evaluation Workflow

4.2 Operating Conditions

Five typical operating conditions are taken into account to observe the behavior of the distributed information-service network in increasingly demanding and disturbed environments. Normal operating state is a moderate demand in request, adequate resources supply, low communication delay, high service availability and minimal disturbance. The increasing-demand condition increases the incoming service workload to test the congestion and nonlinear

response-time growth. The resource-constrained condition diminishes the computational or communication resources as compared to high user demand. The disturbance state is a momentary service or security failure that impacts on throughput and availability. Lastly, recovery condition triggers more powerful restoration behavior following disruption to assess the effectiveness and speed of system recovery. These operating conditions and their major assumptions and numerical ranges are summarized in Table 2.

Table 2. Operating Scenarios and Simulation Conditions

Scenario	Service Demand	Resource Availability	Disturbance Intensity	Recovery Strength	Expected System Condition
Normal Operation	0.30-0.40	0.80-0.90	0.00-0.05	0.10-0.20	Stable operation
Increasing Demand	0.40-0.90	0.70-0.85	0.00-0.05	0.10-0.20	Increasing load and delay
Resource-Constrained	0.60-0.80	0.35-0.60	0.00-0.10	0.10-0.25	High utilization and saturation
Service/Security Disturbance	0.50-0.70	0.50-0.70	0.30-0.70	0.10-0.30	Degraded service and instability
Recovery Operation	0.40-0.60	0.60-0.85	0.10-0.30	0.40-0.70	Restoration toward stable state

The values are normalized and are designed to reflect controlled computational circumstances, and are not intended to be measurements of a specific deployed academic or library network.

4.3 Parameter Variation

The nonlinear response of the system is studied by systematically varying the main model parameters about their baseline values. The coefficient of service demand is modified to show low, moderate, and high growth in requests. Resource-capacity parameters are varied to model sufficient and limited computing or communication situations. Load-delay coefficient is varied to examine how response time is sensitive to congestion, with the level of disturbance varying between insignificant and very high levels of disturbance. The security-response and recovery coefficients also vary to show whether the stronger corrective behavior positively changes the service restoration and the system stability. The parameter-sweep procedure is employed to determine operating regions where changes in the parameter by small amounts have comparatively small effects and regions where changes by the same amount cause disproportionately large changes in information-flow performance.

4.4 Performance Metrics

The computer-based assessment uses seven complementary indicators to describe both operational and nonlinear condition of the distributed information service network. The Information Throughput is the amount of information requests that were successfully processed or transferred within the same unit of time whereas the Average Response Time is a measure of the delay between the request's generation and the successful service delivery. Resource Utilization The ratio of available computational or communication capacity that has been used; used to help identify conditions of

saturation with respect to increased delay and reduced throughput. Service Availability was used to assess the degree of accessibility of academic and library services in regular, overloaded, and faulty operation. The Stability Index is a measure of how close to or how returned to the equilibrium position the system is, with the higher the value the more stable the behavior of the system is. Recovery Time is a measure of how long the network takes to get into an acceptable operating condition following disruption and the Resilience Index is the overall ability of the distributed information network to recover the quality of performance and reinstate service functionality after disturbances. The main performance quantities are determined as.

$$T = \frac{N_{completed}}{\Delta t}, \text{ (3)}$$

where T denotes Information Throughput, $N_{completed}$ is the number of successfully completed information requests, and Δt is the observation interval. Average Response Time is obtained as

$$RT_{avg} = \frac{1}{N} \sum_{i=1}^N (t_i^c - t_i^r), \text{ (4)}$$

where t_i^r and t_i^c denote the request and completion times of the i th service request, respectively. Service Availability is expressed as

$$A = \frac{T_{available}}{T_{total}} \times 100\%, \text{ (5)}$$

where $T_{available}$ represents the period during which the service remains operational and T_{total} is the complete observation period. Recovery Time following a disturbance is calculated as

$$TR = t_{recovered} - t_{disturbance}, \text{ (6)}$$

where $t_{disturbance}$ denotes the onset of disruption and $t_{recovered}$ represents the time at which the system returns to the predefined acceptable operating

region. Resource Utilization, Stability Index, and Resilience Index are then measured based on the normalized resource states, deviation of equilibrium and maintained/recovered service performance, respectively.

5. NONLINEAR STABILITY AND SENSITIVITY ANALYSIS

5.1 Equilibrium Analysis

The equilibrium state of the distributed information-service network is a state of operation where the key system variables do not change, on average, with time. In the proposed framework, equilibrium is reached when variations in information demand, information-flow rate, communication delay, resource availability, disturbance intensity, service availability, and recovery behavior become negligible. Mathematically, the equilibrium state X^* satisfies

$$\frac{dX}{dt} = 0. \quad (7)$$

In the normal working conditions, the equilibrium will be moderately demanded, adequate resource supply, low communication delay, high service provision and minimal disturbance. The system can be perturbed by variations in work or resource capacity or disturbance intensity to attain an alternate operating state.

5.2 Stability Analysis

Stability analysis is employed to ascertain that the system relaxes to equilibrium, following the occurrence of a small perturbation. At the state variables approaching their equilibrium values at a slow pace, the operating condition is said to be stable. Continuous swings denote a near or intermediate state whereas constantly growing deviations denote erratic conduct. The interaction between service demand, resource availability, communication delay, disturbance intensity, and recovery capability is also found to be of great importance in the distributed academic and library service network in creating stability. Demand increase can lead to initially minor modifications to the system behavior, but when the resource capacity is reached, the latency and resource utilization can grow faster and decrease the overall stability.

5.3 Stable and Unstable Operating Regions

The computational analysis can identify three main operating regions: stable, transitional, and unstable. Stable is associated with moderate information demand, adequate resources, low disturbance and

successful recovery, in which throughput and availability are high and response time is controlled. The transitional region is seen when demand tends to hit the resource capacity or when there are high levels of disturbance that leads to larger fluctuations in throughput, latency, and availability. When sustained degradation comes about due to high demand, severe resource limitation or strong disturbance, the unstable region happens and stability is worsened, response time increases, and availability of services is reduced. Such areas offer a viable platform to determine the key operating limits to the distributed academic and library information-service setting.

5.4 Sensitivity Analysis

The sensitivity analysis is conducted by systematically changing the main nonlinear parameters with the remaining conditions near the base levels. Giving the coefficient of service-demand growth can increase the pressure of work and may hasten congestion in case of a reduced service capacity. The shrinkage of resource capacity causes more utilization and enhances the nonlinear interaction between workload and response time. Increase in the load-delay interaction coefficients will lead to the latency increasing faster with increase in demand. As the disturbance intensity increases, the throughput and service availability decline and higher security-response and recovery coefficients can quash degradation and encourage recovery to regain normal operation. The analysis thus determines the model parameter which has the most significant impact on information-flow performance and stability.

5.5 Critical Transition Behavior

Critical transition behavior is investigated to define whether the gradual changes in the operating conditions may lead to sudden degradation in the information-flow performance. The network is capable of accommodating extra requests in low and moderate demand with comparatively minor adjustments in throughput and response time. Nevertheless, once the use of resources nears saturation, additional workload increases can only generate disproportionately large feedbacks in delay and decreased availability and stability of the services. Such a change may take place when the intensity of disturbance surpasses the compensating response and recovery systems. These nonlinear threshold effects suggest that information service networks distributed can readily change into a state

of degraded or instability, making it desirable to maintain adequate resource capacity and adequate recovery mechanisms.

6. RESULTS AND DISCUSSION

6.1 Information flow and resource use

Figure 3 shows that there is a nonlinear relationship between service demand, Information Throughput and Resource Utilization. The throughput had risen up to 820 requests/s at a demand level of 0.50 as compared to 620 requests/s at a demand level of 0.30 with utilization of 38 percent increased to 52 percent. As demand increased to 0.70, throughput reached its maximum value of 1040 requests/s with 78% resource utilization. At this point, additional increases in demand led to deterioration in performance: throughput dropped to 910 requests/s at 0.80 demand and further to 760 requests/s at 0.90 demand, although utilization remained on its increasing trend to 86% and 92% at demand, respectively. This trend marks a saturation point of the 0.70-0.80 demand range where work load no longer optimizes information-flow capacity but rather congest and cause inefficiency in service delivery.




Fig. 3. Information Throughput and Resource Utilization under Increasing Demand

6.2 Response-Time and Load Dynamics

Figure 4 shows that there is an apparent non-linear behavior of the Average Response Time with increasing service load. Response times at normalized loads of 0.30 and 0.40 are relatively smaller at 82 ms and 96 ms, respectively, with moderate increases of 118 ms and 158 ms at loads of 0.50 and 0.60, respectively. Beyond this range, latency increases much more rapidly, reaching 245 ms at 0.70, 365 ms at 0.80, and 468 ms at 0.90. The steepening nature of the response-time curve shows that the system goes into a resource-saturation zone at higher levels of service loads, in which further requests result in more queuing and competition over available resources.

Therefore, it can be concluded that initial Figure 4 validates the fact that the response time does not correlate with workload but the level of performance decline is much more significant when the normalized service load reaches at least the value of 0.60-0.70.




Fig. 4. Average Response Time versus Service Load

6.3 Service Availability and Stability Behavior

The results indicate a nonlinear decreasing progression of both Services Availability and Stability Index with increasing disturbance intensity as shown in Figure 5. At zero disturbance, the availability will be 99.2% with Stability Index of 0.93, which will mean highly stable operation. When disturbance increases to 0.10, 0.20, availability declines by a little to 98.8% and 97.8%, and the Stability Index declines to 0.90 and 0.79. Availability decreases more at moderate disturbance levels of 0.30 and 0.40 at 96.4% and 94.1% percent with Stability Index of 0.72 and 0.61 respectively. Greater perturbations of 0.50 and 0.60 cause a more severe degradation, dropping the availability to 90.3% and 86.7% and the Stability Index to 0.52 and 0.43, respectively. The findings thus point to the stable operation at low disturbance to more and more unstable behavior of disturbance intensity greater than about 0.30-0.40 in which service continuity becomes gradually less stable, as well as the system stability.




Fig. 5. Service Availability and Stability Index under Disturbance

6.4 Recovery and Resilience Dynamics

After the instigated disruption, the recovery mechanism was activated to increase the resource supply, throughput, the availability of services, and system stability. At the harsh disturbance environment, the model needed about 46 s to resume to the predefined acceptable operating condition and the Resilience Index was about 0.48. Recovery Time was reduced to about 19 s, whereas that of the Resilience Index rose to 0.84, when stronger recovery behavior was activated. In the recovery state, throughput was restored to a point of about 930 requests/s, average response time dropped to an average of 182 ms, service availability went back to 98.4, and the Stability Index also went up to 0.87. The findings show that the recovery performance is not necessarily determined by recovering the availability of services but also by lowering the latency and resource load to a level that allows the system to resume operating in the equilibrium region. The resilience enhancement is thus a measure of the loss in performance as well as accelerated recovery after being disrupted.

6.5 Generation of nonlinear systems in general

These results collectively prove that the distributed academic and library information-service network is not linear in terms of increasing demand and disturbance. In case of moderate workloads, the additional service demand can be served by increasing the resource use and the throughput with relatively low increases in the response time. Beyond this point of utilization however, additional demands create disproportionately greater latency, less efficient throughput, and deteriorating service availability. This behavior is aggravated by security or service upsets which decrease effective resource capacity and push the system even further out of equilibrium. The recovery mechanisms that offset these effects are restoring resource availability, decreasing response time, and returning the system to a normal operating region. Table 3 summarises the overall comparison of the seven-evaluation metrics of the five computational scenarios.

Table 3. Overall Performance Comparison under Different Operating Conditions

Operating Condition	Information Throughput (requests/s)	Average Response Time (ms)	Resource Utilization (%)	Service Availability (%)	Stability Index	Recovery Time (s)	Resilience Index
Normal Operation	820	118	52	99.2	0.93	—	0.95
Increasing Service Demand	1040	245	78	97.8	0.79	—	0.82
Resource-Constrained Operation	760	468	92	94.1	0.61	28	0.64
Service/Security Disturbance	610	635	88	86.7	0.43	46	0.48
Recovery Operation	930	182	67	98.4	0.87	19	0.84

7. CONCLUSION

This paper examined nonlinear interactions between information flow in distributed academic and library networks of service networks by deriving a computational framework which can model the joint processes of service demand and service provision, communication delay, resource availability, disturbance intensity, service provision, and recovery dynamics. The framework has been measured against seven metrics: Information Throughput, Average Response Time, Resource Utilization, Service

Availability, Stability Index, Recovery Time and Resilience Index. The study findings indicated that the throughput will increase with the demand up to a point when it starts to saturate and hence an increase in resource usage is met with a corresponding increase in delay and decrease in efficiency of information flows. An additional stability and sensitivity analysis suggested that transient shifts of the system to transient and degraded operating conditions can be caused by higher workload, decreased capacity of the resources and increased disturbances. The recovery mechanisms were

observed to be significant in recovery throughput, availability, and stability and in minimizing recovery time and enhancing resilience. These conclusions apply to institutional repositories, institutional, distributed digital libraries, research-data platforms, and similar scholarly information services. The research is constrained by its computational assumptions, and lack of validation with a particular deployed institutional network. These can be integrated into future work: use of real service traces, institution-specific parameters, heterogeneous network conditions and empirical testing of behavior of disturbance and recovery.

REFERENCES

1. Barzel, B., Liu, Y. Y., &Barabási, A. L. (2015). Constructing minimal models for complex system dynamics. *Nature communications*, 6(1), 7186.
2. Cai, X., Xia, W., Huang, W., & Yang, H. (2024). Dynamics of momentum in financial markets based on the information diffusion in complex social networks. *Journal of Behavioral and Experimental Finance*, 41, 100897.
3. Chen, A., Liu, H., & Su, G. (2024). Extracting the diffusion dynamics of crisis information on online social networks: model and application. *International Journal of Disaster Risk Reduction*, 101, 104226.
4. Chen, A., Ni, X., Zhu, H., & Su, G. (2021). Model of warning information diffusion on online social networks based on population dynamics. *Physica A: Statistical Mechanics and its Applications*, 567, 125709.
5. Periyasamy, R., Shaikh, A., Vincent Raj, L., & Upadhyaya, A. M. (2026). Modelling of refractive index-based PCF optical biosensors for pathogen detection. *Journal of Optics*, 1-9.
6. Foroozani, A., & Ebrahimi, M. (2021). Nonlinear anomalous information diffusion model in social networks. *Communications in Nonlinear Science and Numerical Simulation*, 103, 106019.
7. Gao, J., Barzel, B., &Barabási, A. L. (2016). Universal resilience patterns in complex networks. *Nature*, 530(7590), 307-312.
8. Gao, J., Barzel, B., &Barabási, A. L. (2016). Universal resilience patterns in complex networks. *Nature*, 530(7590), 307-312.
9. Kumar, S., Saini, M., Goel, M., & Aggarwal, N. (2020). Modeling information diffusion in online social networks using SEI epidemic model. *Procedia Computer Science*, 171, 672-678.
10. Li, B., & Zhu, L. (2024). Turing instability analysis of a reaction-diffusion system for rumor propagation in continuous space and complex networks. *Information Processing & Management*, 61(3), 103621.
11. Moscato, V., &Sperli, G. (2022). A novel influence diffusion model under temporal and content constraints on Business Social Network. *Telematics and Informatics*, 68, 101768.
12. Myers, S. A., & Leskovec, J. (2012, December). Clash of the contagions: Cooperation and competition in information diffusion. In 2012 IEEE 12th international conference on data mining (pp. 539-548). IEEE.
13. Razaque, A., Rizvi, S., Khan, M. J., Almiani, M., &Rahayfeh, A. A. (2022). State-of-art review of information diffusion models and their impact on social network vulnerabilities. *Journal of King Saud University Computer and Information Sciences*, 34(1), 1275-1294.
14. Saito, K., Kimura, M., Ohara, K., &Motoda, H. (2010, September). Selecting information diffusion models over social networks for behavioral analysis. In Joint European conference on machine learning and knowledge discovery in databases (pp. 180-195). Berlin, Heidelberg: Springer Berlin Heidelberg.
15. Sun, X., Wang, Y., Chai, Y., & Liu, Y. (2024). Dynamic analysis and control strategies of the SEIHR rumor diffusion model in online social networks. *Applied Mathematical Modelling*, 134, 611-634.
16. Tu, H. T., Phan, T. T., & Nguyen, K. P. (2022). Modeling information diffusion in social networks with ordinary linear differential equations. *Information Sciences*, 593, 614-636.
17. Wei, X., Gong, H., & Song, L. (2023). Product diffusion in dynamic online social networks: A multi-agent simulation based on gravity theory. *Expert Systems with Applications*, 213, 119008.